



NEW! Polyurethane on Nylon Center Wheels with AISI 304 Stainless Steel Forks

- 3", 4", & 5 x 1-¼" wheel diameter
- Double ball bearing raceway
- Load capacity up to 440 lbs
- AISI 304 stainless steel components
- Poly on white nylon core, 94-Shore A
- Stainless steel roller bearing and bushing
- Seal guard on upper raceway
- Available in swivel, rigid, and total lock casters



Product Number	Description	Wheel Diameter (mm)	Wheel Width (mm)	Bearing	Top Plate Size (mm)	Top Plate Hole Spacing (mm)	Total Height (mm)	Loading (kgs)
SS322UNY	Stainless Steel Swivel	80	30	Stainless	105x85	82x62 / 78x58	105	150 kgs
SS422UNY		100	36				128	200kgs
SS522UNY		125	37	Roller			156	200 kgs
SS329UNY	Stainless Steel Rigid	80	30	Stainless	105x85	82x62 / 78x58	105	150 kgs
SS429UNY		100	36				128	200 kgs
SS529UNY		125	37	Roller			156	200 kgs
SS322UNY-SWB	Stainless Steel Swivel + Total Lock	80	30	Stainless	105x85	82x62 / 78x58	105	150kgs
SS422UNY-SWB		100	36				128	200 kgs
SS522UNY-SWB		125	37	Roller			156	200 kgs

Application:

Food processing, laboratory equipment, medical equipment, animal cages, pharmaceutical equipment, utility carts, restaurants, kitchen, laundry equipment and other wet and/or corrosive environments.



Contact **Colson** for other wheel options